

Machine operator: study guide

Manufacturing, production, maintenance, and quality · suite apt-156-machine-operator · generated 2026-09-15T15:24:51.876Z

Detail	Value
Title	Machine operator: study guide
Generated	2026-09-15T15:24:51.876Z
Fixture/version	apt-156-machine-operator
Sector	Manufacturing, production, maintenance, and quality
Guide version	v2

Private practice result. Not an official exam certificate, employer decision, hiring signal, admissions decision, or guaranteed outcome. Scores stay on this device unless you export them.

Answer keys and scoring logic stay server-side and are never included in any download or export.

How to use this guide

This file contains the whole study outline for this suite: every skill it draws on, the full lesson for each of those skills, worked examples, practice tips, a glossary, and where each piece of material comes from. Nothing here is a summary of a page you still have to visit.

1. Read the skills section end to end once, without timing yourself.
2. Work the guided practice mode for the suite, using the practice tips as a checklist.
3. Move to the mini-test only when guided practice feels unhurried.
4. Sit the full simulation last, once, in the conditions you expect on the day.

Practice attempts are stored on the device you used, never on an account. Exporting a result is the only way anything leaves that device.

Practice modes and durations

Practice modes for Machine operator

Mode	Duration	What it is for
Guided practice	15 minutes	Untimed, with feedback after every item.
Mini-test	18 minutes	A short timed set for checking pace.
Full simulation	45 minutes	Full length and full time, in one sitting.

- Start guided practice:
<https://learn.novusstreamsolutions.com/aptitude/practice/new?bank=apt-156-machine-operator&mode=guided>
- Start mini-test:
<https://learn.novusstreamsolutions.com/aptitude/practice/new?bank=apt-156-machine-operator&mode=mini>
- Start full simulation:
<https://learn.novusstreamsolutions.com/aptitude/practice/new?bank=apt-156-machine-operator&mode=full>

Skills covered, in full

This suite draws on 5 skill constructs. Each one below carries its complete lesson.

Mechanical comprehension

Forces, motion, gears, pulleys, levers, fluids, pressure, and basic machines.

Mechanical comprehension is the ability to predict what a physical system will do (which way a gear turns, how hard you have to pull, how far the load actually rises) from forces, moments and the simple machines, rather than from a memorised formula sheet. It carries real weight in apprenticeship entry batteries, military technical selection, and screening for maintenance, machine operation and rigging roles. The same reasoning is daily work on site: sizing a jack, choosing a block-and-tackle arrangement, deciding why a belt slips under load but not at idle. Practice here is device-local: no account, and nothing leaves this device unless you export it.

What you should be able to do after this lesson:

1. Balance moments about a pivot (effort x effort arm = load x load arm) and name whether a given tool is a first-, second- or third-class lever.
2. Work out the speed, torque and rotation direction of a driven gear from tooth counts, including what an idler gear does and does not change.
3. Count the rope parts that support a moving block to get the mechanical advantage of a pulley system, then state how much rope must be pulled per metre of lift.
4. Apply pressure = force / area to a hydraulic jack and predict the piston-travel penalty that comes with the force gain.
5. Predict rpm across a belt or chain drive from pulley or sprocket diameters, and say when slip breaks the prediction.
6. State the trade-off that governs every simple machine: multiplied force always costs distance, and friction always makes the delivered advantage smaller than the ideal one.

Worked examples and pitfalls

Levers: balance the moments, then name the class: A wheelbarrow carries 60 kg whose centre of mass sits 0.4 m from the wheel axle, and you grip the handles 1.2 m from that same axle. Take moments about the axle: lift force x 1.2 m = 60 kgf x 0.4 m, so the lift force is $60 \times 0.4 / 1.2 = 20$ kgf, about 196 N. The mechanical advantage is simply the arm ratio, $1.2 / 0.4 = 3$. Two traps live in this item. The first is measuring the load arm from your hands instead of from the fulcrum; the arm is always the perpendicular distance to the pivot, and the pivot here is the wheel contact, not the barrow body. The second is calling it a first-class lever because that is the one everyone pictures. A wheelbarrow is second class: fulcrum at one end, load in the middle, effort at the far end, which is why its mechanical advantage is always greater than one. Compare tweezers or a pair of tongs, where the effort sits between fulcrum and load: that is third class, mechanical advantage below one, and you are deliberately trading force away to buy speed and control at the tip. Your own forearm lifting a weight is the same arrangement, which is why a 5 kg dumbbell loads the biceps far more than 5 kg.

Gear trains: tooth counts set speed, meshes set direction: A 12-tooth driver turning at 300 rpm meshes directly with a 36-tooth gear. The ratio is driven teeth over driver teeth, $36/12 = 3:1$, so the output turns at $300/3 = 100$ rpm and, ignoring friction, carries about three times the torque. One external mesh reverses rotation, so the output turns opposite to the driver. Now drop a 20-tooth idler between them. Step it through: $300 \times 12/20 = 180$ rpm at the idler, then $180 \times 20/36 = 100$ rpm at the output. The overall ratio is unchanged at 3:1, the idler's tooth count cancels, but there are now two external meshes, two reversals, so the output turns the SAME way as the driver. That is the whole reason idlers are fitted. The tempting wrong answer

treats the idler as another reduction stage and reports 180 rpm or some product of both ratios. The check that never fails: only the first and last gear in a simple train affect the ratio, and the direction depends on whether the number of external meshes is odd (reversed) or even (same). An internal or ring mesh, as in a planetary set, does not reverse at all.

Pulleys: count the rope parts that carry the load: A 200 kg load, about 1,962 N. Hung from a single pulley bolted to a beam, the pulley only changes the direction you pull; both rope parts still meet at a fixed axle, the mechanical advantage is 1, and you pull the full 200 kgf. Hang the pulley on the load instead, with one rope end anchored above and the other in your hands, and two rope parts now support the moving block: mechanical advantage 2, effort about 100 kgf or 981 N, but you must pull 2 m of rope for every 1 m the load rises. Build a tackle with four parts supporting the moving block and the effort falls to $200/4 = 50$ kgf, about 490 N, at the cost of 4 m of rope pulled per metre of lift. The trap is counting sheaves instead of supporting parts. A three-sheave arrangement gives three parts if the dead end is made off to the fixed block and four if it is made off to the moving block, and the answer differs by 33 percent. The second trap is treating the figure as delivered force: real sheaves lose a few percent each to bearing and rope friction, so quoted mechanical advantage is the ideal velocity ratio, and the effort you actually feel is higher.

Hydraulics: pressure is shared, force and travel are traded: A jack has a 2 square centimetre input piston and a 50 square centimetre output ram. Push the small piston with 100 N and the pressure in the fluid is $100 / 2 = 50$ N per square centimetre, which is 500 kPa. Pascal's principle says every part of the confined fluid sees that same 500 kPa, so the large ram feels $50 \text{ N/cm}^2 \times 50 \text{ cm}^2 = 2,500 \text{ N}$. Mechanical advantage 25. Nothing is free: fluid is effectively incompressible, so volume in equals volume out. A 25 cm stroke on the small piston moves $2 \times 25 = 50$ cubic centimetres, and 50 cubic centimetres spread over a 50 square centimetre ram raises it 1 cm. Twenty-five centimetres of pumping buys one centimetre of lift: exactly the force-times-distance bargain a lever strikes. Candidates lose this item by assuming both pistons travel the same distance, or by concluding the jack manufactures energy. A related item asks about a tank: the pressure at the bottom depends on the height of fluid above and its density, not on the width of the vessel, so a narrow 3 m standpipe reads the same bottom pressure as a 3 m deep swimming pool.

Belts and chains: same belt speed, different rpm: A motor pulley 100 mm in diameter runs at 1,450 rpm and drives a 250 mm pulley through an open V-belt. The quantity that is genuinely shared is belt speed, not rpm, so the driven pulley turns at $1,450 \times 100/250 = 580$ rpm. Note the direction of the ratio: with gears you divide by driven teeth, with belts you divide by driven diameter, and the arithmetic looks the same only because both are proportional to circumference. An open belt drives both pulleys the same way; a crossed belt reverses the driven pulley, which is the entire point of the classic crossed-belt diagram item. The trap is slip. A flat or V-belt under an overload slips, so the driven speed falls below 580 rpm while the motor holds 1,450: the symptom of a glazed belt or a weak tensioner. A chain or a toothed timing belt physically cannot slip a tooth without damage, which is why camshaft and indexing drives use them and why a belt-driven answer and a chain-driven answer to the same question can legitimately differ.

Springs in series and parallel: the answer most people reverse: Two identical coil springs, each 20 N/mm. Mount them side by side, both carrying the same load, and they act in parallel: stiffness adds to 40 N/mm, so a 400 N load compresses the pair $400/40 = 10$ mm. Now stack them end to end, in series. Each spring carries the whole 400 N, force is not split down a chain, so each deflects $400/20 = 20$ mm and the total is 40 mm. The combined stiffness is $400/40 = 10$ N/mm, half of one spring. Most candidates reverse the two because 'series' sounds like the case where things add. Two reliable checks: in parallel the arrangement is always stiffer than one spring, and in series it is always softer than the softest spring. That is also why suspension designers add a helper spring in parallel to raise rate under load, and why a long slender bolt clamps more forgivingly than a short stubby one carrying the same preload.

How to practise this skill

- Sketch the free body and mark the pivot before writing a single number. Mechanical items are lost by choosing the wrong fulcrum far more often than by mis-multiplying.
- Fix the three lever classes to a tool you can picture (pliers and a see-saw for first class, a wheelbarrow and a nutcracker for second, tweezers and your own forearm for third), and say the class out loud before answering.
- Sanity-check every answer against the work rule: if a machine multiplies force it must divide distance. An answer where the effort both moves less and is smaller than the load is wrong somewhere.
- Convert units before you multiply, not after. A moment computed with millimetres on one side and metres on the other is off by a thousand and looks perfectly plausible.
- For any direction question, walk the mesh or the belt with a finger: each external gear pair reverses, an internal or ring mesh does not, an open belt keeps direction and a crossed belt flips it.
- Work untimed until you can explain the reasoning aloud, then add the clock. Attempts are recorded on this device only, so a messy first pass through gear trains costs you nothing but time.

Glossary

Moment (torque): A force multiplied by the perpendicular distance from its line of action to the pivot, in newton-metres. A body is in rotational balance when clockwise moments equal anticlockwise moments about the same point.

Fulcrum: The pivot a lever turns about. Its position relative to the load and the effort defines the lever class and therefore whether the tool multiplies force or multiplies movement.

Mechanical advantage: Output force divided by input force. Ideal mechanical advantage is the geometric figure; actual mechanical advantage is what you get after friction, and it is always lower.

Velocity ratio: Distance moved by the effort divided by distance moved by the load. In a lossless machine it equals the ideal mechanical advantage, which is why force gain always costs travel.

Gear ratio: Driven teeth divided by driver teeth. A ratio above one reduces speed and multiplies torque; only the first and last gear of a simple train affect it.

Idler gear: A gear placed between driver and driven purely to add a mesh. It reverses the output direction and bridges a distance without altering the overall ratio.

Pascal's principle: Pressure applied to a confined fluid is transmitted undiminished to every part of it, which is what lets a small piston at high pressure produce a large force on a bigger ram.

Head: The height of a fluid column above a point. Pressure at depth is density x gravity x height and is independent of the vessel's width or shape.

Study this next

- Mechanical comprehension skill hub:
<https://learn.novusstreamsolutions.com/aptitude/skills/mechanical-comprehension>
- Millwright and industrial mechanic suite:
<https://learn.novusstreamsolutions.com/aptitude/tests/millwright-and-industrial-mechanic>
- Spatial reasoning lesson: <https://learn.novusstreamsolutions.com/aptitude/skills/spatial-reasoning/lesson>
- Skilled trades, maintenance and repair careers:
<https://learn.novusstreamsolutions.com/careers/families/skilled-trades-maintenance-and-repair>
- Encyclopedia search: simple machine:
<https://learn.novusstreamsolutions.com/search?q=Simple%20machine>
- Mechanical comprehension lesson on Novus Learn:
<https://learn.novusstreamsolutions.com/aptitude/skills/mechanical-comprehension/lesson>

Where this material comes from

- Worked examples written for Novus Learn from standard introductory mechanics: moments about a pivot, gear ratios from tooth counts, rope-part counting for tackle, and Pascal's principle.
- Terminology checked against the public Wikipedia articles 'Simple machine', 'Lever', 'Gear train' and 'Pascal's law'. Definitions only; every number and item above is original.
- Novus Learn aptitude construct registry (catalog seed) for the construct scope and related suite mapping.
- Public educational framing only: not affiliated with any official exam board, publisher or employer, and no copyrighted test item is reproduced.

Educational preparation only. Novus Learn does not administer official exams and does not guarantee scores or hiring outcomes.

Numerical reasoning

Arithmetic, fractions, percentages, ratios, rates, estimation, word problems, and number relationships.

Numerical reasoning is the ability to take a small set of supplied numbers (a price list, a staffing table, a fuel figure), and reach a defensible answer in around ninety seconds without a formula sheet. It is the most widely used quantitative section in graduate, management and public-sector screening, and it appears in banking, retail, armed forces and healthcare entry batteries alike. The arithmetic itself is deliberately ordinary: percentages, ratios, rates and averages. What is actually being measured is whether you pick the right operation quickly, keep the units straight, and answer the question that was asked rather than the one you started computing. Practice here is device-local: no account, and nothing leaves this device unless you export it.

What you should be able to do after this lesson:

1. Move between fractions, decimals, percentages and ratios on sight, and pick whichever form makes a given item fastest (12.5 percent as one eighth, 33.3 percent as one third).
2. Apply percentage change in both directions, including recovering an original figure from a post-increase total, and combine successive changes multiplicatively rather than by adding them.
3. Split a total in a stated ratio by counting parts first, and work backwards from a stated difference between two shares.
4. Solve rate problems (speed, unit price, consumption, combined work rates) by carrying units through every intermediate line so the units of the answer prove the method.
5. Produce a one-significant-figure estimate before computing, and use it to eliminate the distractors built from the common wrong operations.
6. Read a multi-step stem and name, in one sentence, the single quantity the final question asks for before touching the numbers.

Worked examples and pitfalls

Reverse percentages: the item most candidates get backwards: A subscription price rose by 15 percent and now stands at 57.50 pounds. What was it before? The correct move is to divide, not subtract: the new price is 115 percent of the old, so the old price is $57.50 / 1.15 = 50.00$. Check it forwards: 15 percent of 50 is 7.50, and $50 + 7.50 = 57.50$. The tempting wrong answer takes 15 percent of the NEW figure, $0.15 \times 57.50 = 8.625$, and reports 48.88. That distractor is always on the option list because it is what most people do under time pressure, and it is wrong by 2.25 percent, small enough to look plausible. The same asymmetry drives the successive-change item: a price that rises 20 percent and then falls 20 percent does not return to where it started. Multiply the factors: $1.20 \times 0.80 = 0.96$, a net fall of 4 percent. Starting at 500 pounds you get 600 then 480, not 500. Percentages compose by multiplication; they never add.

Ratio splits: count the parts before you divide: A 4,830 pound budget is split between three teams in the ratio

3:5:6. Add the parts first: $3 + 5 + 6 = 14$. One part is $4,830 / 14 = 345$. The shares are $3 \times 345 = 1,035$, $5 \times 345 = 1,725$ and $6 \times 345 = 2,070$, and they sum back to 4,830, which is the check you should always run. Two classic failures. The first is dividing by 3 because there are three teams. That gives 1,610 each and ignores the ratio entirely. The second is treating 5 as a fraction and computing five sixths or five fourteenths of something other than the total. The more interesting version of this item gives you a difference instead of the total: 'the second team receives 690 pounds more than the first, what is the whole budget?' The difference between the shares is $5 - 3 = 2$ parts, so one part is $690 / 2 = 345$, and the budget is $14 \times 345 = 4,830$. Same number, reached from the other end, and the arithmetic is trivial once you have made the parts explicit.

Rates and units: 2 h 15 min is 2.25, not 2.15: A delivery van covers 174 km in 2 hours 15 minutes. Average speed is distance over time, and the time must be in hours: 15 minutes is $15/60 = 0.25$ h, so $174 / 2.25 = 77.3$ km/h. Type 2.15 into the calculator instead and you get 80.9 km/h: an error of roughly 4.7 percent that sits comfortably inside the plausible range and will match one of the options. Now extend it. The van consumes 8.6 litres per 100 km, so the trip needs $174 \times 8.6 / 100 = 14.964$ litres, and at 1.48 pounds per litre that is $14.964 \times 1.48 = 22.15$ pounds. Notice the units doing the work: (km) $\times$ (L / 100 km) leaves litres; (L) $\times$ (pounds / L) leaves pounds. If your intermediate line has km still attached at the end, you have divided when you should have multiplied. Write the unit next to every number and the method checks itself.

Unit pricing: normalise before you compare: Three pack sizes of the same fluid. Pack A: 750 ml for 3.60 pounds. Pack B: 2 litres for 9.40. Pack C: 1.5 litres for 7.20. Convert all three to price per litre. A: $3.60 / 0.75 = 4.80$ per litre. B: $9.40 / 2 = 4.70$. C: $7.20 / 1.5 = 4.80$. So B is cheapest by 10p a litre, and A and C are identical despite looking like different deals. The 'bigger pack is cheaper' heuristic happens to hold here but is not a rule, and test writers know it. Half of these items are built specifically so the largest pack loses. Now add the multibuy that these questions love: pack A is on three-for-two. Three packs give 2.25 litres for the price of two, 7.20 pounds, which is $7.20 / 2.25 = 3.20$ per litre and beats everything. The trap in the multibuy version is dividing by the number of packs paid for rather than the volume received.

Combined work rates: add rates, never times: Printer A completes a 3,000-page run in 50 minutes; printer B completes the same run in 75 minutes. Running together, how long? Convert to rates: A prints $3,000 / 50 = 60$ pages per minute, B prints $3,000 / 75 = 40$ pages per minute, and together they print 100 pages per minute, so the job takes $3,000 / 100 = 30$ minutes. Verify by counting output: in 30 minutes A produces 1,800 pages and B produces 1,200, which is 3,000 exactly. The two wrong answers you will see on the option list are 62.5 minutes (the average of 50 and 75) and 125 minutes (the sum). Both are impossible on inspection: two machines working together must finish faster than the faster machine alone, so any answer above 50 minutes is wrong before you compute anything. The general form is $1 / (1/50 + 1/75)$, and it is worth being able to write that line directly, but the sanity bound catches the error faster than the algebra does.

Estimate first, then compute: killing distractors in ten seconds: 'A department spent 847,300 pounds in 2024. In 2025 the budget fell by 12.5 percent. What was the 2025 spend?' Options: 741,387.50 / 953,212.50 / 105,912.50 / 762,570. Estimate before anything else: 12.5 percent is exactly one eighth, one eighth of roughly 850,000 is roughly 106,000, so the answer is roughly 744,000. That single line eliminates three options. 953,212.50 applied the change upwards. 105,912.50 is the size of the reduction, not the resulting spend: the 'answered the wrong question' distractor, and the most commonly selected wrong option on items of this shape. 762,570 is a 10 percent cut, planted for anyone who misread the rate. Exact working: $847,300 \times 7/8 = 5,931,100 / 8 = 741,387.50$. Doing it as a fraction avoids the decimal multiplication altogether. Learn the fraction equivalents cold (12.5 percent is $1/8$, 16.7 percent is $1/6$, 37.5 percent is $3/8$, 62.5 percent is $5/8$) because a fraction turns most percentage items into one division.

How to practise this skill

- Memorise the fraction-to-percentage table up to eighths and twelfths. Almost every 'nasty' percentage on these tests is a clean fraction in disguise, and the fraction route is two or three times faster than decimal

multiplication.

- Write the unit beside every intermediate number, including the ones you keep in your head. Most numerical errors on timed sections are unit errors, not arithmetic errors, and units are the only cheap way to catch them.
- Rehearse reverse percentages as their own drill until dividing by 1.15 feels more natural than subtracting 15 percent. It is a single, identifiable technique that accounts for a disproportionate share of lost marks.
- Before selecting, re-read the last clause of the stem out loud. 'By how much did it fall' and 'what was it after the fall' have different answers, and both are always on the option list.
- Keep an error log with four columns (misread the question, wrong operation, unit slip, arithmetic slip), and tally which one you actually commit. Three sessions is usually enough to show that one column dominates, and that is the column to train.
- Work untimed until your method is stable, then add the clock in stages: generous, then realistic, then 20 percent tighter than the real test. Attempts stay on this device, so a slow first pass costs nothing.

Glossary

Percentage point: The arithmetic difference between two percentages. A rate moving from 4 percent to 5 percent rises by one percentage point but by 25 percent in relative terms; questions specify which they want and the two answers are both on the option list.

Reverse percentage: Recovering an original amount from a figure that already includes a percentage change, by dividing by the multiplier (1.15 for a 15 percent rise, 0.88 for a 12 percent fall) rather than subtracting the percentage from the new figure.

Multiplier (decimal factor): The single number a quantity is multiplied by to apply a percentage change: 1.20 for plus 20 percent, 0.80 for minus 20 percent. Successive changes are handled by multiplying the factors, which is why plus 20 then minus 20 gives 0.96, not 1.

Ratio part: One unit of a ratio split. Dividing the total by the sum of the ratio terms gives the value of one part; every share and every difference between shares is then a whole number of parts.

Unit rate: A quantity expressed per one of something: price per litre, pages per minute, litres per 100 km. Comparisons are only valid once every option has been converted to the same unit rate.

Combined rate: The sum of two or more individual rates working simultaneously. Times cannot be added or averaged; only rates add, and the combined time is the total work divided by the combined rate.

Significant figure estimate: Rounding every input to one meaningful digit to get an approximate answer in a few seconds. Its purpose is not accuracy but elimination: it removes any option that is off by a factor or has the sign of the change wrong.

Distractor: A wrong option written deliberately to match a specific predictable error: subtracting instead of dividing, reporting the change instead of the result, averaging instead of combining rates. Recognising the pattern is often faster than recomputing.

Study this next

- Numerical reasoning skill hub: <https://learn.novusstreamsolutions.com/aptitude/skills/numerical-reasoning>
- Numerical reasoning practice in the Cognitive Skills Lab: <https://learn.novusstreamsolutions.com/cognitive-skills/numerical-reasoning>
- Data interpretation lesson: <https://learn.novusstreamsolutions.com/aptitude/skills/data-interpretation/lesson>
- Office numeracy suite: <https://learn.novusstreamsolutions.com/aptitude/tests/office-numeracy>
- Finance, accounting and insurance careers: <https://learn.novusstreamsolutions.com/careers/families/finance-accounting-and-insurance>
- Numerical reasoning lesson on Novus Learn:

Where this material comes from

- All worked figures above were written and checked for Novus Learn. Every division, ratio split and rate calculation in this lesson was verified by recomputing it in the reverse direction.
- Conventions only (percentage point, unit rate, significant figures) cross-checked against standard public references such as the Wikipedia articles 'Percentage', 'Ratio' and 'Rate (mathematics)'. No item text is drawn from any published test.
- Novus Learn aptitude construct registry (catalog seed) for construct scope and suite mapping.
- Public educational framing only: not affiliated with any official exam board, publisher or employer, and no copyrighted test item is reproduced.

Educational preparation only. Novus Learn does not administer official exams and does not guarantee scores or hiring outcomes.

Safety judgment

Hazard recognition, safe sequencing, escalation, and risk controls.

Practise recognizing hazards and choosing a safe, proportionate response: protect people, control immediate exposure, use the correct reporting path, and verify that the control is effective.

What you should be able to do after this lesson:

1. Separate a hazard from the likelihood, severity, and exposure that shape its risk.
2. Choose an immediate control that stays within the person's training and authority.
3. Recognize when work should pause and when a supervisor, emergency process, or qualified specialist is needed.

Worked examples and pitfalls

Worked scenario: a damaged machine guard: A guard is loose before a scheduled run. Do not operate the machine or improvise a repair beyond your authorization. Keep people away, isolate or label the equipment only as procedure permits, report the defect to the responsible person, and wait for an approved inspection or repair. A deadline does not remove the hazard.

Risk-triage questions: Ask: what can cause harm, who is exposed now, how severe could the outcome be, what control is available, and who has authority to apply it? The safest answer is not always the most dramatic option; it is the option that controls the real exposure without creating a new hazard.

How to practise this skill

- Treat warnings, permits, isolation rules, and personal protective equipment as parts of a system, not interchangeable shortcuts.
- Do not ask an untrained person to investigate a hazard simply because they are nearby.
- In real work, site procedures and qualified safety direction override any general preparation heuristic.

Glossary

Hazard: A source or situation with the potential to cause harm.

Risk: A judgement about possible harm that considers likelihood, severity, and exposure.

Control: A measure that removes a hazard or reduces exposure to it under an approved process.

Study this next

- Occupational safety and health:
<https://learn.novusstreamsolutions.com/search?q=Occupational%20safety%20and%20health>
- Hazard: <https://learn.novusstreamsolutions.com/search?q=Hazard>
- Risk assessment: <https://learn.novusstreamsolutions.com/search?q=Risk%20assessment>
- Safety judgment lesson on Novus Learn:
<https://learn.novusstreamsolutions.com/aptitude/skills/safety-judgement/lesson>

Where this material comes from

- Novus Learn original safety-critical, hazard-recognition, and operational suite scenarios.
- Novus educational framework: identify the hazard, protect people, control exposure, report, and verify.

Educational preparation only. Novus Learn does not administer official exams and does not guarantee scores or hiring outcomes.

Attention and concentration

Sustained focus, selective attention, and accuracy under time pressure.

Attention and concentration is the skill of still noticing on minute forty of a checking block as reliably as you did on minute two, and of pointing the noticing at the right thing when two things compete. It has three distinguishable parts - selective attention, sustained attention or vigilance, and divided attention - and assessments load them differently: cancellation and checking tasks load vigilance, conflict tasks load selection, and dispatch-style monitoring loads division. It is the construct that decides whether a records clerk, a dispatcher, an air-side controller or a quality inspector catches the one wrong digit in a shift. Practice here is device-local, with no account and nothing uploaded.

What you should be able to do after this lesson:

1. Count occurrences of a target in a dense string without double-counting or losing your place, using a fixed scan path rather than free looking.
2. Separate hits, misses and false alarms in your own results and work out whether you are set too eager or too cautious for the scoring rule in force.
3. Predict where in a long block your error rate will rise, and schedule micro-resets against that curve instead of pushing through it.
4. Recognise a transposition error, the class that survives a same-characters gist check and is therefore missed most often.
5. Explain why an automatic process such as reading interferes with a controlled one, and use that to anticipate which distractors will actually cost you time.
6. Run a two-stream monitoring task by alternating on a fixed cadence rather than attempting genuine simultaneity.

Worked examples and pitfalls

A cancellation count you can actually check: Count every 7 in this row: 4 7 1 7 7 3 9 7 2 8 7 5 7 6 0 7.

Working left to right and tapping once per hit: hits at the second, fourth, fifth, eighth, eleventh, thirteenth and sixteenth positions. That is seven sevens. Two error modes produce nearly all the wrong answers. The first is the adjacent pair - the 7 7 at positions four and five gets counted once, because the eye takes a repeated character as one perceptual object. The second is losing the place after the 9, where the visually similar 9 and 7 force a moment of re-checking and the scan restarts a character early, producing an over-count of eight. The defence for both is a fixed scan path with a physical anchor: a fingertip or cursor moving one character at a time, never jumping back. Re-scanning to check is the thing that creates the double-count, so

if you must verify, verify by counting a second time from the RIGHT-hand end and comparing totals, never by re-reading part of the row.

Hits, misses and false alarms: the eager candidate loses: A checking batch contains 300 records, 40 of which are genuinely faulty. Candidate A flags 46 records and 36 of them are truly faulty. Hits 36, misses 40 minus 36 equals 4, false alarms 46 minus 36 equals 10. Candidate B flags 38 and 34 are truly faulty: hits 34, misses 6, false alarms 4. On hit rate alone A wins, 36 out of 40 which is 90 percent against B's 34 out of 40 which is 85 percent. Now apply the scoring rule that most checking tasks actually use, where a false alarm cancels a hit: A scores 36 minus 10 equals 26, B scores 34 minus 4 equals 30. B wins by four despite catching two fewer faults. This is why 'flag anything that looks odd' is bad advice on a scored checking task, and why the first thing to read on a checking item is whether wrong flags are penalised. Your response criterion - how much evidence you demand before flagging - is adjustable, and it should be set from the scoring rule, not from your temperament.

The transposition that passes every gist check: Compare these two lines and decide whether they match. Invoice 4820-7391-06. Invoice 4820-7931-06. They do not: the middle group reads 7391 in the first and 7931 in the second, with the 3 and the 9 swapped. Transpositions are the most-missed error class in record checking for a structural reason - the character SET is identical, the length is identical, the first and last characters of the group are identical, so every fast check the visual system runs comes back clean. Substitutions and omissions change the character inventory and get caught; transpositions do not. Two habits raise the catch rate. Read digits in fixed groups of two rather than as a whole number, so 73-91 against 79-31 becomes a mismatch at the first group instead of a subtle difference somewhere in a four-digit blur. And check groups in a deliberately non-natural order - last group, first group, middle group - because reading left to right lets the confirmation you built at the start carry you through the middle, which is exactly where the swap is usually planted.

Conflict: why reading fights you: The classic demonstration is Stroop's, published in 1935: the word RED printed in blue ink, with the instruction to name the ink colour. Naming takes measurably longer, and errors go up, because reading a familiar word is automatic and cannot be switched off, so the automatic response has to be suppressed before the controlled one can be produced. The same conflict has a numeric version you can test on yourself in a second: how many characters are in the string 4 4 4? The answer is three, and the digit 4 pulls at you the entire way. In an assessment this appears wherever the salient feature and the asked-for feature come apart - a chart where the tallest bar is not the answer to the question, a form where the highlighted field is not the one being verified, a row where the bold total is not what the stem requested. The practical move is to name the target feature out loud before you look - 'ink colour', 'character count', 'the value for March' - because pre-loading the target biases selection before the automatic reading response gets a chance to win.

Where the errors actually appear in a 45-minute block: Errors in a long checking block are not spread evenly. Mackworth's 1948 clock-watching study established the pattern that gives the effect its name: detection declines over a prolonged watch, with the sharpest deterioration early rather than at the very end. Practically, on a 45-minute self-timed checking block, expect your per-minute error rate in minutes 20 to 45 to run visibly above minutes 1 to 20 even though nothing about the material changed, and expect the subjective sense of effort to lag the actual decline, so it will not feel like you are getting worse. Two things work against it. Break the block into three fifteen-minute segments with a ten-second reset between them - look away, unfocus, breathe out - which costs thirty seconds of a 45-minute block, about one percent of the time, and buys back more than that in caught errors. And score your practice by segment rather than as one number, because a single overall accuracy figure hides exactly the information you need: whether your problem is skill, which shows as flat error rate, or endurance, which shows as a rising one.

Two streams: alternate on a cadence, do not try to merge: A dispatch-style monitoring task: keep a running total of the numbers announced on channel one while watching channel two for the code word AMBER. Genuine simultaneity is not available - the two tasks compete for the same control resource - so the choice is

not whether to alternate but whether to alternate deliberately or accidentally. Deliberate looks like this: fix the arithmetic to a rhythm, updating the total only at each announcement and holding a single number between updates, which frees the gaps for channel two. If the total is 34 and the next announcement is 7, you spend under a second reaching 41 and then you are free again. Accidental looks like re-deriving the running total from the beginning because you did not trust it, which locks up the whole window and is when AMBER goes past unheard. The measurable failure of divided attention is almost never a failure to hear the target; it is a failure to have any spare capacity at the moment it arrived. The related phenomenon worth knowing is inattention blindness, illustrated by Simons and Chabris in 1999: an unexpected and perfectly visible event is missed entirely when attention is committed to a counting task.

How to practise this skill

- Fix your scan path before you start, and never re-scan backwards to double-check. Backward re-scanning is what produces both double-counts and lost places; if you need to verify a count, run it again from the other end and compare.
- Read the scoring rule before the first item. Whether false alarms are penalised changes the correct strategy completely, and a criterion set for the wrong rule costs more marks than slow reading does.
- Check numeric strings in fixed groups of two or three and in a deliberately shuffled group order. Transpositions are the errors that survive whole-string comparison, and they are the ones planted on purpose.
- Time your practice in segments and log accuracy per segment, not per session. A flat error rate means you need speed; a rising one means you need endurance and breaks, and the two problems have opposite fixes.
- Name the target feature out loud before each conflict item. Pre-loading the relevant dimension is the cheapest available defence against the salient-but-wrong answer.
- Practise with an actual distractor present rather than in silence. A test hall has movement, coughing and page-turning, and attention practice in perfect quiet trains a condition you will not meet.

Glossary

Selective attention: Prioritising one source or feature while suppressing competing ones. It is what fails when the visually salient element of a display captures the response instead of the requested one.

Sustained attention (vigilance): Maintaining detection performance over a long, low-event period. It is the capacity that checking, monitoring and inspection tasks are really sampling.

Vigilance decrement: The decline in detection performance over a prolonged watch, typically steepest early in the block. Mackworth's 1948 clock test is the standard public reference.

Divided attention: Handling two streams that compete for control. Performance is best modelled as fast alternation with a switch cost, not as genuine parallelism.

Hit, miss, false alarm, correct rejection: The four outcomes of any detection decision: flagging a real fault, missing one, flagging a clean record, and correctly leaving a clean record alone. Any honest accuracy claim needs at least the first three.

Response criterion: How much evidence you require before flagging. Shifting it trades misses against false alarms without changing your underlying sensitivity, which is why it must be set from the scoring rule.

Stroop interference: The slowing that occurs when an automatic response, such as reading a word, conflicts with the requested response, such as naming its ink colour. Named for Stroop's 1935 experiments.

Inattention blindness: Failing to notice a fully visible, unexpected event because attention is committed elsewhere - the effect Simons and Chabris demonstrated in 1999 with a counting task.

Study this next

- Attention and concentration skill hub:
<https://learn.novusstreamsolutions.com/aptitude/skills/attention-concentration>
- Cognitive Skills Lab: attention practice:
<https://learn.novusstreamsolutions.com/cognitive-skills/attention-concentration>
- Emergency dispatch and 911 communications suite:
<https://learn.novusstreamsolutions.com/aptitude/tests/emergency-dispatch-and-911-communications>
- Error detection lesson: <https://learn.novusstreamsolutions.com/aptitude/skills/error-detection/lesson>
- Perceptual speed lesson: <https://learn.novusstreamsolutions.com/aptitude/skills/perceptual-speed/lesson>
- Attention and concentration lesson on Novus Learn:
<https://learn.novusstreamsolutions.com/aptitude/skills/attention-concentration/lesson>

Where this material comes from

- Character strings, invoice comparisons, batch counts and monitoring scenarios above are written for Novus Learn. All figures are original and no published test item is reproduced.
- Terminology and directions of effect follow widely published work: Mackworth (1948) on the vigilance decrement, Stroop (1935) on response conflict, Simons and Chabris (1999) on inattention blindness, and the standard hit/miss/false-alarm framing from signal detection theory. Concepts only; no result figures are attributed to those studies.
- Novus Learn aptitude construct registry (catalog seed) for construct scope and suite mapping.
- Public educational framing only - not affiliated with any official exam board, publisher or employer, and not a clinical, diagnostic or attention-disorder screening measure.

Educational preparation only. Novus Learn does not administer official exams and does not guarantee scores or hiring outcomes.

Technical reasoning

Applied technical principles, diagrams, tools, systems, measurements, and troubleshooting.

Technical reasoning is what sits above any single trade: reading a system diagram for what it actually does, isolating a fault by measurement instead of by guesswork, and taking the governing number off a drawing or a nameplate without importing assumptions. It is assessed in HVAC, instrumentation, mechatronics, process-operator and engineering-technician selection, and it is the construct that best predicts whether someone can diagnose an unfamiliar machine. Employers care about it because part-swapping is expensive and half-splitting is not. Practice sessions here stay on your device unless you choose to export them.

What you should be able to do after this lesson:

1. Trace a process or signal diagram end to end and state, for a given symptom, which components could physically cause it and which could not.
2. Isolate a fault by half-splitting a chain of stages, and say how many measurements a chain of a given length should take.
3. Convert a dimension with asymmetric tolerance into an acceptance window and decide whether a measured part passes, can be reworked, or is scrap.
4. Match a measuring instrument to a required resolution, and distinguish an instrument's resolution from its accuracy.
5. Describe a closed control loop as sensor, controller, setpoint, actuator and feedback, then design the one measurement that separates a sensor fault from an actuator fault.
6. Read the qualifier attached to a rated number (duty cycle, working load limit, working pressure, nominal versus maximum), and apply it correctly.

Worked examples and pitfalls

Half-splitting beats swapping parts: A conveyor will not stop when its photo-eye is blocked. The chain is: sensor, field cable, junction box, PLC input card, PLC program, output card, interposing relay, contactor. Eight places the signal can die. Swapping parts one at a time means four or five attempts on average, since the culprit is equally likely to sit anywhere in the eight, and every attempt costs a part. Half-splitting starts in the middle instead: watch the PLC input LED while a colleague blocks the beam. If it toggles, the sensor, field cable, junction box and input card are all proven good in a single observation, and eight candidates become four. Force the output in the PLC and watch the contactor: if it pulls in, the output card, interposing relay and contactor are good as well, so the fault is in the program logic rather than the hardware. Three checks resolve eight stages, because each check halves the remaining suspects. The trap is starting at whichever end is easiest to reach, which resolves one stage per check instead of half of them. The second trap is the sentence 'I replaced the sensor and it still fails', that proves only that the sensor was not the fault, at the price of a part and an hour.

Tolerance: in spec, or scrap?: A drawing calls a shaft 25.00 mm with a tolerance of plus 0.05 and minus 0.10. That is an asymmetric tolerance, so the acceptance window runs from 24.90 mm to 25.05 mm and the nominal is not at its centre. A part measuring 24.92 mm is inside the window and passes, even though it is below nominal: the most common wrong rejection on this style of item, made by anyone who silently reads the tolerance as plus or minus 0.05. A part at 25.06 mm fails by 0.01 mm, but it fails oversize, so material can still be removed and it is rework rather than scrap. A part at 24.85 mm fails undersize and there is no recovering it. One more layer the better items include: if you took that 25.06 reading on a caliper with 0.02 mm resolution, the reading is at the very limit of what the instrument can resolve, and the honest next step is to re-measure with a micrometer before anyone scraps or reworks anything.

Reading a system diagram: what can actually cause this?: A tank fill line is drawn as supply, isolation valve V1, strainer, pump P1, check valve, control valve CV1, tank. A high-level switch LSH-1 is wired to close CV1. The reported symptom is that the tank overfilled. Work the path between the measurement and the element that stops flow: a CV1 that has stuck open, an LSH-1 that never actuated, and a broken wire in the LSH-1 loop are all consistent with the symptom. A blocked strainer is not: restricting the inlet reduces flow, and no amount of restriction causes an overfill. Nor is the check valve, whose function is to prevent reverse flow, not forward flow. Candidates pick the strainer because it is the component they know fouls in service, which is a memory of maintenance history rather than a reading of the diagram. The discipline that earns the mark is directional: a component can only be responsible if it lies on the causal path AND its failure mode pushes the system in the direction of the symptom.

Instrument choice: resolution is not accuracy: A steel rule resolves to roughly 0.5 mm. A vernier caliper marked 0.02 mm resolves to 0.02 mm. A 0 to 25 mm micrometer resolves 0.01 mm on the thimble, or 0.001 mm if it carries a vernier. A dial indicator reads 0.01 mm of relative movement but tells you nothing about absolute size without a reference. Asked to verify a 25.00 mm shaft with a tolerance of plus or minus 0.02 mm, the tolerance band is 0.04 mm wide: two divisions on that caliper, which is not enough to judge anything reliably. The workshop convention is that the instrument should resolve to about a tenth of the tolerance band, here 0.004 mm, so even the micrometer is marginal and comparison against gauge blocks is the defensible answer. The trap the item is built around is a digital display: showing four decimal places is a statement about resolution, not accuracy. An uncalibrated digital caliper will report 25.0000 mm with total confidence and be 0.03 mm out.

Closed loop: which element failed?: A room is meant to hold 21 degrees Celsius. A thermostat containing the sensor and the controller drives a valve on a radiator. The symptom: the room reaches 28 degrees Celsius and the valve stays open. Three explanations survive first inspection. The sensor reads low so the controller still believes the room is cold, the valve is mechanically jammed open, or the controller output has failed in the on state. One measurement separates them. Put an independent thermometer beside the thermostat. If the thermostat displays 17 degrees while the thermometer reads 28, the sensor is lying and everything

downstream is behaving correctly. If the thermostat displays 28 and is still calling for heat, the sensor is fine and the fault is in the controller or the valve, which you then split by checking whether the valve actuator is being energised. The tempting non-answer is 'the room is too hot, so lower the setpoint'. That treats the symptom, and if the sensor reads seven degrees low the loop will simply settle seven degrees high again at the new setpoint.

Nameplates: read the qualifier, not just the number: A welding machine is rated 200 A at 40 percent duty cycle over a ten-minute period. That means four minutes of arc time and six minutes of cooling in every ten, at the full 200 A. It does not mean 40 percent of 200 A, and it does not mean 40 percent of an hour. Both wrong readings feel entirely natural, which is why they make good distractors. Run the machine continuously at 200 A and the thermal cut-out will open. The same discipline transfers across the whole trade: a hoist's working load limit is not its breaking load, a hose's working pressure is not its burst pressure, a motor's service factor describes a short-term overload allowance and not a continuous rating, and a pump curve's flow figure is quoted at a stated head. Whenever an item hands you a number in a table or on a plate, underline the qualifier printed next to it before you calculate anything; the wrong options are usually built by dropping exactly one qualifier.

How to practise this skill

- Trace every diagram with a pencil from input to output and name each block as you pass it. Technical items punish skimming far harder than they punish slow arithmetic.
- Rehearse half-splitting on systems you already know (a home network that has dropped out, a car that will not crank), and count the checks. The habit transfers to the test intact.
- Underline the qualifier beside every number a question supplies: per hour, at 20 degrees Celsius, at 40 percent duty, nominal, maximum. That single mark-up defuses most distractors.
- Convert the whole question to one unit system in one pass before calculating, rather than converting each intermediate result and accumulating rounding.
- Train yourself to state what a measurement PROVES rather than what it reads. '12 V present at the coil' proves the supply and the whole upstream path; it says nothing about whether the coil itself is good.
- Keep a running list of the schematic symbols and component names you personally keep getting wrong, and drill only those. Five focused minutes beats another full untargeted set, and your attempt history stays local to this device so the list is yours alone.

Glossary

Half-split fault finding: Testing at the midpoint of a chain of stages so that each measurement eliminates half the remaining suspects. A chain of eight stages resolves in about three checks rather than four swaps.

Tolerance band: The distance between the upper and lower acceptance limits of a dimension. A tolerance written as plus 0.05 and minus 0.10 has a 0.15 mm band that is not centred on the nominal.

Resolution: The smallest change an instrument can display. A four-decimal readout has fine resolution and may still be inaccurate if the instrument is out of calibration.

Accuracy: How close a reading is to the true value, established by calibration against a traceable standard. Independent of resolution, and the property that decides whether a part passes.

Interlock: A condition wired or programmed to inhibit an action until it is satisfied, such as a guard-door switch that prevents a motor start while the door is open.

Closed-loop control: A control arrangement where a sensor measures the process, a controller compares that measurement to a setpoint, and an actuator drives the process until the difference closes.

Duty cycle: The proportion of a stated period during which equipment may operate at a stated output, for example 40 percent of a ten-minute period, after which it must cool.

Schematic versus pictorial diagram: A schematic shows function and connection logic with no regard to

physical layout; a pictorial or exploded view shows physical arrangement and assembly order but hides the logic.

Root cause: The condition whose removal stops a failure recurring, as opposed to the symptom, which is only what became visible.

Study this next

- Technical reasoning skill hub: <https://learn.novusstreamsolutions.com/aptitude/skills/technical-reasoning>
- HVAC and refrigeration suite: <https://learn.novusstreamsolutions.com/aptitude/tests/hvac-and-refrigeration>
- Instrumentation and control suite:
<https://learn.novusstreamsolutions.com/aptitude/tests/instrumentation-and-control>
- Engineering and technical design careers:
<https://learn.novusstreamsolutions.com/careers/families/engineering-and-technical-design>
- Encyclopedia search: troubleshooting: <https://learn.novusstreamsolutions.com/search?q=Troubleshooting>
- Technical reasoning lesson on Novus Learn:
<https://learn.novusstreamsolutions.com/aptitude/skills/technical-reasoning/lesson>

Where this material comes from

- Diagnostic and metrology examples written for Novus Learn from general maintenance practice: binary-search fault isolation, asymmetric dimensional tolerance, and the ten-to-one instrument selection convention.
- Terminology checked against the public Wikipedia articles 'Troubleshooting', 'Engineering tolerance', 'Accuracy and precision' and 'Control loop'. Definitions only; every scenario above is original.
- Novus Learn aptitude construct registry (catalog seed) for the construct scope and related suite mapping.
- Public educational framing only: not affiliated with any official exam board, publisher or employer. Ratings and limits described here are illustrative and never override the equipment documentation in front of you.

Educational preparation only. Novus Learn does not administer official exams and does not guarantee scores or hiring outcomes.

Recommended preparation

- Practice technical reasoning:
<https://learn.novusstreamsolutions.com/aptitude/skills/technical-reasoning/lesson>
- Build numerical reasoning:
<https://learn.novusstreamsolutions.com/aptitude/skills/numerical-reasoning/lesson>
- Practice safety judgement: <https://learn.novusstreamsolutions.com/aptitude/skills/safety-judgement/lesson>

Answer keys, scoring and privacy

Answer keys and scoring logic stay server-side and are never included in any download or export.

Formal suite answer keys and scoring logic stay on the server and are not part of any download, in any format. Downloadable keys exist only for the open, untimed practice material (the practice packs on the puzzles, cognitive-skills and reasoning practice lab pages), where the answers are already public teaching content.

Novus Learn needs no account. Your practice history lives in this browser's storage on this device, and is sent to a server only if you create an account and switch on backup. This file contains no attempt, session or result link, so it is safe to share.

Private practice result. Not an official exam certificate, employer decision, hiring signal, admissions decision, or guaranteed outcome. Scores stay on this device unless you export them.

Answer keys and scoring logic stay server-side and are never included in any download or export.

Source: <https://learn.novusstreamsolutions.com/aptitude/tests/machine-operator/study-outline>